



Pluto 54



Pluto 54 - High frequency surface luminaires are a range of high efficiency luminaires designed to accommodate T5 or T8 fluorescent lamps. They are suitable for general lighting in retail and commercial applications.

- 5 year ballast warranty as standard .
- Complete with prismatic or opal polycarbonate diffuser.
- High quality steel body, screw type end caps
- Tamper proof allen key screw available upon request, standard versions supplied with cross type screw
- Emergency versions available upon request.
- LOR of over 69%.
- Standard model not suitable for dimming but dimmable versions are available upon request.
- Supplied fitted with European branded control gear
- IP54 rated and ideal for hospitals and schools.
- Supplied less lamps as standard

TECHNICAL DATA:



Tegral
Quality Lighting

Product Code	Description	Wattage	Primary Lumen Output	Size
TS158PR/IP54	T8, 1500mm Surface IP54 with Prismatic Cover	1x58	5200	1583x162x71
TS158OP/IP54	T8, 1500mm Surface IP54 with Opal Cover	1x58	10400	1583x162x71
TS258PR/IP54	T8, 1500mm Surface IP54 with Prismatic Cover	2x58	5200	1583x162x71
TS258OP/IP54	T8, 1500mm Surface IP54 with Opal Cover	2x58	10400	1583x162x71
TS170PR/IP54	T8, 1800mm Surface IP54 with Prismatic Cover	1x70	6300	1883x162x71
TS170OP/IP54	T8, 1800mm Surface IP54 with Opal Cover	1x70	12600	1883x162x71
TS270PR/IP54	T8, 1800mm Surface IP54 with Prismatic Cover	2x70	6300	1883x162x71
TS270OP/IP54	T8, 1800mm Surface IP54 with Opal Cover	2x70	12600	1883x162x71

Product Code	Description	Wattage	Primary Lumen Output	Size
TS128PR/IP54	T5, 1200mm Surface IP54 with Prismatic Cover	1x28	2640	1283x165x58
TS228PR/IP54	T5, 1200mm Surface IP54 with Prismatic Cover	2x28	5280	1283x165x58
TS154PR/IP54	T5, 1200mm Surface IP54 with Prismatic Cover	1x54	4460	1283x165x58
TS254PR/IP54	T5, 1200mm Surface IP54 with Prismatic Cover	2x54	8920	1283x165x58
TS135PR/IP54	T5, 1500mm Surface IP54 with Prismatic Cover	1x35	3650	1593x165x58
TS235PR/IP54	T5, 1500mm Surface IP54 with Prismatic Cover	2x35	7300	1593x165x58
TS149PR/IP54	T5, 1500mm Surface IP54 with Prismatic Cover	1x49	4450	1593x165x58
TS249PR/IP54	T5, 1500mm Surface IP54 with Prismatic Cover	2x49	8900	1593x165x58
TS128OP/IP54	T5, 1200mm Surface IP54 with Opal Cover	1x28	2640	1283x165x58
TS228OP/IP54	T5, 1200mm Surface IP54 with Opal Cover	2x28	5280	1283x165x58
TS154OP/IP54	T5, 1200mm Surface IP54 with Opal Cover	1x54	4460	1283x165x58
TS254OP/IP54	T5, 1200mm Surface IP54 with Opal Cover	2x54	8920	1283x165x58
TS135OP/IP54	T5, 1500mm Surface IP54 with Opal Cover	1x35	3650	1593x165x58
TS235OP/IP54	T5, 1500mm Surface IP54 with Opal Cover	2x35	7300	1593x165x58
TS149OP/IP54	T5, 1500mm Surface IP54 with Opal Cover	1x49	4450	1593x165x58
TS249OP/IP54	T5, 1500mm Surface IP54 with Opal Cover	2x49	8900	1593x165x58

Add to end of Product Code	Application
/D	1-10v Analogue Dimmable
/DD	DSI/Push Dim
/DALI	DALI Dimmable
/M3	3 Hour Emergency
/MS	Inbuilt Microwave Sensor (35w/49w options only)
/NL	Inbuilt NiteLite



- Supplied Less lamp
- Lumen outputs are approximate & subject to change

For more information on our Tegral brand of products, please contact us

Tegral Lighting Ltd
Unit 4 Myson Way
Raynham Road Industrial Estate
Bishops Stortford
Herts, CM23 5JZ

Integral Lighting Ltd
Unit 99 Barrow Road
Dublin Ind Est
Glasnevin, Dublin 11

E-mail: salesuk@tegral-lighting.com
Tel: +44 (0)1279 461888/908
Fax: +44 (0)1279 460115

E-mail: sales@tegral-lighting.com
Tel: +353 (01) 8309684/85/86
Fax: +353 (01) 8309932



Tegral
Quality Lighting

www.tegral-lighting.com