ORBIT TWO

CE RoHS SUPPLIED WITH EUROPEAN BRANDED CONTROL GEAR 1-10V DIMMABLE DALI DIMMABLE PUSH DIMMABLE TRIAC DIMMABLE

A range of highly efficient ceiling or wall mounted traditional style bulkheads. Suitable for use in apartment blocks, bathrooms, bedrooms, carehomes, corridors, hotels, stairwells and all commercial or domestic applications.

STBH12WH/84

CTBH18WH

KEY FEATURES

- 50,000hr life expectancy
- CRI > 80
- IP66 Rated
- IK10 Rated
- Manufactured with quality materials and reliable driver
- PF > 0.90
- Zero maintenance

MATERIALS

- European branded driver
- Polycarbonate base & polycarbonate diffuser
- Silicon gasket seal, moisture & dustproof up to IP66

ACCESSORIES AVAILABLE

- Can be fitted with inbuilt corridor function, please add /CF on end of product code
- Can be fitted with inbuilt photocell or microwave sensor. Please add /PC or /MS to end of product code
- Dimmable versions available. (See dimmable options)
- Emergency versions available. Add M3 for standard 3 hour emergency or ST for self test 3 hour emergency.
- Night Light available. Please add NL to end of product code.

ADDITIONAL INFORMATION

- Come with wall/ceiling mounting stainless steel brackets for quick installation
- Complete with hinged geartray for easy installation
- Side cable entry with 16mm gland

DIMMABLE OPTIONS

- /D for 1-10V dimmable
- /DD for DSI digital dimmable
- /DL for Dali and switch dimmable
- /TD for leading/trailing edge dimmable

WARRANTY

5 years

IP RATING

IP66



Orbit Two

PRODUCT CODE CIRCULAR	DESCRIPTION	WATTAGE (W)	SIZE Dia x H (mm)	LIGHT SOURCE	NET LUMEN OUTPUT	LUMEN PER CIRCUIT WATT
CTBH12BK/83	Circular black bulkhead 3000k	12W	300 x 100	SMD LED	1040lm	> 85
CTBH12BK/84	Circular black bulkhead 4000k	12W	300 x 100	SMD LED	1040lm	> 85
CTBH12WH/83	Circular white bulkhead 3000k	12W	300 x 100	SMD LED	1040lm	> 85
CTBH12WH/84	Circular white bulkhead 4000k	12W	300 x 100	SMD LED	1040lm	> 85
CTBH18BK/83	Circular black bulkhead 3000k	18W	350 x 120	SMD LED	1460lm	> 80
CTBH18BK/84	Circular black bulkhead 4000k	18W	350 x 120	SMD LED	1460lm	> 80
CTBH18WH/83	Circular white bulkhead 3000k	18W	350 x 120	SMD LED	1460lm	> 80
CTBH18WH/84	Circular white bulkhead 4000k	18W	350 x 120	SMD LED	1460lm	> 80
CTBH24BK/83	Circular black bulkhead 3000k	24W	400 x 120	SMD LED	2085lm	> 85
CTBH24BK/84	Circular black bulkhead 4000k	24W	400 x 120	SMD LED	2085lm	> 85
CTBH24WH/83	Circular white bulkhead 3000k	24W	400 x 120	SMD LED	2085lm	> 85
CTBH24WH/84	Circular white bulkhead 4000k	24W	400 x 120	SMD LED	2085lm	> 85
CTEL12BK/84	Circular black eyelid 4000k	12W	350 x 120	SMD LED	950lm	> 75

PRODUCT CODE OVAL	DESCRIPTION	WATTAGE (W)	SIZE Dia x H (mm)	LIGHT SOURCE	NET LUMEN OUTPUT	LUMEN PER CIRCUIT WATT
OTBH10BK/84	Oval Black bulkhead 4000k	10W	300 x 100	SMD LED	950lm	> 90
OTBH10WH/84	Oval White bulkhead 4000k	10W	300 x 100	SMD LED	950lm	> 90

PRODUCT CODE SQUARE	DESCRIPTION	WATTAGE (W)	SIZE Dia x H (mm)	LIGHT SOURCE	NET LUMEN OUTPUT	LUMEN PER CIRCUIT WATT
STBH12BK/84	Square Black bulkhead 4000k	12W	290 x 100	SMD LED	950lm	> 75
STBH12WH/84	Square White bulkhead 4000k	12W	290 x 100	SMD LED	950lm	> 75

CTEL12BK/84

OTBH landscape