



Black RAL9005



Grey RAL7016



Description

Range of highly efficient and effective asymmetrical wall packs. Suitable for general lighting in apartment blocks, schools, walkways and many more external applications.

Key Features

- IP65 as standard
- Dimmable and Emergency options available (Standard, Self test, Dali Emergency available)
- Durable aluminium body and polycarbonate diffuser
- 5 years warranty.

Applications

- External Balconys
- Pathways
- Schools and Colleges

Electrical Information

Model No.	ASWP/4
Power Consumption(±5%)	13/18/28w
Power Supply	European brand driver
Input Voltage	220-240 VAC, 50-60Hz
Power Factor	>0.9
Driver Type	Constant current with European brand, or 1-10v , Triac, Dali

Optic Information

LED Type	SMD LED
Luminous Flux (±10%)	
Efficacy(4000K Ra80)	1800lm/2500lm/3500lm
Diffuser Type	Opal polycarbonate
Efficiency	> 130lm per watt
CCT	4000k
Color Rendering Index	Ra80
Beam Angle	Asymmetrical

Dimensions and Mounting

Dimensions	319x165x265mm
Output Voltage Range	42v
Mounting Option	Surface
Material	Polycarbonate Diffuser Aluminium body
Finish	Black (RAL9005) or Grey (RAL7016)
SCDM	<6
IK Rating	IK10
IP Rating	IP65

Lifespan and Warranty

Operating Temperature	-10°C to + 35°C
Life Time of LED @Ta=25°C	> 60,000hrs L80B20
Warranty	5 years

Accessories

www.tegral-lighting.com