



Electrical Information	
Model No.	TLB120
Typ.Power	113W
Input Voltage	AC 220-240V, AC100-240 VAC, 50 / 60 Hz
Power Factor	>0.95
Insulation Type	Class I
Driver Type	Constant Current (CC)
Control	Dimmable / Photocell/ DALI Dimmable/ZHAGA/ Microwave Sensor/ PIR Sensor

Optic Information	
LED Type	LED 3737
Efficacy (4000K RA80)	125lm/W
Correlated Color Temperature	4000K or 5700K
Color Rendering Index	RA80
Beam Angle	120 degrees
Lumens	14260lm

Dimensions and Structure	
Product Dimension	620x270x65
Luminaire Net Weight	2.25kg
Mounting Option	Suspended
Material	Aluminum Alloy and polycarbonate Pmma lens
Finish	White
Fixture Color	White
IK Rating	IK06
IP Rating	IP40

Lifespan and Warranty	
Operating Temperature	-20°C to + 50°C
Life Time of LED @Ta=25°C	76000hrs-L80B10
Warranty	5 Years

New Features	
<p>* Please consult us for details.</p>	

**Description**

A highly versatile lowbay that can be used in many applications including , retail, showrooms and warehouses.

**Key Features**

- simple installation.
- High output lumen efficiency, up to 133lm/W
- The housing is made of 100% aluminum alloy (ADC12)
- Powder coating with strong antiST36-corrosion.
- Easy to maintain.
- Adjustable elevation.

**Applications**

- Conference Halls
- Retail
- Showrooms
- Warehouses

**Photometry**